## **Outdoor-Cabinet**



- Universal operating conditions based on construction with mounting plate
- Userfriendly access through wideopening and lockeable doors (approx. 105°)
- High protection level, with rubber gasket and projecting rain shield
- No corrosion (aluminium)

Our outdoor cabinets are developed and specially designed for use as terminal and connection cabinet.

An integrated rain shield increases the protection class.

All external fittings are made of stainless steel.

This cabinet is designed for wall mounting. To avoid vacuum or high pressure all outdoor cabinets are equipped with pressure regulation plugs. In case of bedewing problems we provide an internal heating system.

The door is equipped with gas-filled shock absorbers to avoid banging doors.

Finally the cabinet is equipped with a water drain on either side of the bottom.

Furthermore, there is a removable bolt flange plate in the bottom (bottom 170 x 700 mm, cutout 130 x 645 mm) facilitating the cable connection.

## Type list

Туре	Item no.	Door stop	Size W/H/D	Weight	Protection level	Colour
OUT-DOOR 900	ST-009367	right	900/770/200	27 kg	IP 55	DB 601
OUT-DOOR 1500	ST-013699	double door	1500/770/200	45 kg	IP 55	DB 601

Westhaus Energietechnik GmbH Hermann Mende Str. 5-7 D-01099 Dresden

Phone: +49 351 20920 100 Fax: +49 351 20920 112

sales@wh.de www.wh.de